



1787
Bleached Sand



1913
Sand Dollar



1347
Beige



1318
White/Black



1320
Refined White
Multi



1789
Sugar Cane



1314
White/Grey




1862
Cane



1324
Cool Gray



1310
White/Blue



1786
Cloudy Day



1323E
Playful
White/Multi



1337
Desert Tan



1356
Oatmeal



1985
Sun Baked



1824
Sand Castle



1367
Sierra Beige



1231
Chocolatta



1365
Dark Taupe



1345
Beige Taupe



1262
Dusty Trail



1364
Dark Gray



1374
Charcoal



1248
Saddle Brown



1336
Yellow



1245
Brown Derby



1608
Orange Crush



1240
Limeaid




1241
Forest Fern



1298
Clover



1275
Pine Forest



1350
Blue Lagoon



1243
Atlantic Blue



1370
Hudson Blue



1379
Red



1238
Ocean Tide



I250
African Violet



I278
Merlot



I328
Black/White



I242
Cheddar



Características

Modulación: Ancho 30,5 cms.

Largo: 30,5 cms.

Espesor: 3,2 mm.

La caja contiene 45 palmetas (4,18 m²) y pesa 28 kg.

Estabilidad dimensional.

Palmeta vinílica homogénea modular de Tarkett, para alto tráfico comercial.

Composición Through Chip.

Diseño direccional.

100% reciclable.

Usos

Bodegas.

Supermercados.

Salud.

Educación.

Residencias Adulto Mayor

Expressions™ VCT

Technical Data	Standards	VCT	Solids & Feature Strips	Feature Strips
Type of Floor Covering		Vinyl Composition Tile	Vinyl Composition Tile	Sizes, Quantities & Weights
Classification	ASTM F 1066	Class 2 Through Pattern	Class 1 Solid Color	1/4" x 24" 100 pieces per ctn - 200 lin. ft. (60.96 lin. m per ctn) 6 lbs per ctn (2.7 kg)
Total Thickness		1/8" (3.2 mm)	1/8" (3.2 mm)	1/2" x 24" 75 pieces per ctn - 150 lin. ft. (45.72 lin. m per ctn) 9 lbs per ctn (4 kg)
Static Load Limit	ASTM F 970	150 psi	150 psi	1" x 24" 50 pieces per ctn - 100 lin. ft. (30.48 lin. m per ctn) 11.5 lbs per ctn (5.2 kg)
Tile Size		12" x 12" (305 mm x 305 mm)	12" x 12" (305 mm x 305 mm)	2" x 24" 25 pieces per ctn - 50 lin. ft. (15.24 lin. m per ctn) 12 lbs per ctn (5.4 kg)
Weight/sq. ft./m ²		1.4 lbs sq. ft. (14.0 lbs. m ²)	1.4 lbs sq. ft. (14.0 lbs. m ²)	4" x 24" 15 pieces per ctn - 30 lin. ft. (9.14 lin. m per ctn) 14 lbs per ctn (6.3 kg)
Carton Quantity		45 tiles = 45 sq. ft. (4.18 m ²)	45 tiles = 45 sq. ft. (4.18 m ²)	6" x 24" 15 pieces per ctn - 30 lin. ft. (9.14 lin. m per ctn) 21 lbs per ctn (9.5 kg)
Carton Weight		64 lbs (29.0 kg)	64 lbs (29.0 kg)	
Flammability	ASTM E 648	Class 1 >0.45 CRF	Class 1 >0.45 CRF	
Smoke Density	ASTM E 662	<450	<450	
Slip Resistance SCOF	ADA Compliant			
Chemical Resistance		Good	Good	
Colors		40 Standard Price	4 Premium Price Solids	
Warranty		5 Year LIMITED Warranty. See tarkettna.com/expressions for complete warranty information.	5 Year LIMITED Warranty. See tarkettna.com/expressions for complete warranty information.	
Maintenance		Conventional VCT Maintenance 3-5+ coats of finish*	Conventional VCT Maintenance 3-5+ coats of finish*	

* Depending upon use of the floor.

Please visit tarkettna.com/expressions for the most updated specifications, and installation, cleaning and maintenance instructions.

How to Order: (XXXX) Color Number