






Grey Beige
6002



Light Grey
6035



Medium Beige
6051



Fresh Blue
6055



Dark Red
6059



Tangerine
6058

HETEROGENEOUS ACOUSTIC VINYL

Tapiflex Evolution

Specification

Acoustic flexible vinyl floorcovering with a new foam backing on a non woven glass fiber stabilized carrier. This HE vinyl is reinforced with TopClean XP™ and built-in fungistatic and bacteriostatic treatment.

Product standard: EN 651.



CERTIFICATION & CLASSIFICATION	STANDARDS	Salt & Pepper	Sand	Spaghetti XXL, Spaghetti, Spice & Candy, Havane - Uni, Pastille - Draft
Type of floorcovering	ISO 11638 - EN 651			Heterogeneous acoustic vinyl
Wear Layer Binder Content	ISO 10582			Type I
UPEC Classification	EN ISO 717-2			U4P3E2/3C2
Impact sound reduction	EN ISO 717-2			ΔL_w 17 dB
Acoustical Improvement Classification	NF S31-074			$L_{n,e,w} = < 65$ dB - Class A
	ISO 10874 - EN 685			34

TECHNICAL CHARACTERISTICS	STANDARDS	Salt & Pepper	Sand	Spaghetti XXL, Spaghetti, Spice & Candy, Havane - Uni, Pastille - Draft
Wear layer thickness	ISO 24340 - EN 430	1.00 mm	0.90 mm	0.70 mm
Surface Treatment		TopClean XP™	TopClean XP™	TopClean XP™
Total thickness	ISO 24346 - EN 428	3.35 mm	3.20 mm	3.05 mm
Abrasion Group / mm³	EN 660-2	Group T : ≤ 2.0	Group T : ≤ 2.0	Group T : ≤ 2.0
Total weight / m²	ISO 23997 - EN 430	3570	3440	3210
Form of delivery	ISO 24344 - EN 426	Sheet (rolls)		
				approx. 23 running metres x 200 cm

TECHNICAL PERFORMANCES	STANDARDS	Salt & Pepper	Sand	Spaghetti XXL, Spaghetti, Spice & Candy, Havane - Uni, Pastille - Draft
Dimensional stability	ISO 23999 - EN 434			Length + width < 0.10%
Reaction to fire	EN 13501-1			B _{fl} s1 on any A2 _{fl} or A1 _{fl} substrate C _{fl} s1 on any derivative wood substrate
Residual indentation	ISO 24343-1 - EN 433			Required value: ≤ 0.20 mm Average measured value: 0.08 mm Best measured value*: 0.07 mm
Castor wheel test	ISO 4918 - EN 425			No damage
Furniture leg	EN 424			No damage
Curl resultant to heat	ISO 23999 - EN 434			≤ 8 mm
Electrostatic properties	EN 1815 / EN 1081			< 2 kV on concrete / R ₁ > 10 ⁹ Ω
Hygiene				Does not contribute to infection spreading
Chemical resistance	ISO 26987 - EN 423			High resistance
Thermal resistance	EN 10456			0.04 m² K/W
Underfloor heating				Suitable
Light fastness	EN ISO 105-B02			≥ 6
Slip resistance	DIN 51130 / EN 13893			R9 / μ ≥ 0.3
Colours		12	9	Spaghetti XXL: 2 - Spaghetti: 8 Spice & Candy: 18, Havane: 5 - Uni: 4, Pastille: 2 - Draft: 6

HETEROGENEOUS COMPACT VINYL

Acczent Evolution

Specification

Compact flexible vinyl floorcovering. This HE vinyl is reinforced with TopClean XP™ and built-in fungistatic and bacteriostatic treatment.

Product standard: ISO 10582.



CERTIFICATION & CLASSIFICATION	STANDARDS	Salt & Pepper	Sand	Spaghetti XXL, Spaghetti, Spice & Candy, Havane - Uni, Pastille - Draft
Type of floorcovering	ISO 10582			Heterogeneous compact vinyl
UPEC Classification	EN ISO 717-2			Type I
Classification	ISO 10874 - EN 685			U4P3E2/3C2
				34-43

TECHNICAL CHARACTERISTICS	STANDARDS	Salt & Pepper	Sand	Spaghetti XXL, Spaghetti, Spice & Candy, Havane - Uni, Pastille - Draft
Wear layer thickness	ISO 24340 - EN 430	1.00 mm	0.90 mm	0.90 mm
Surface Treatment		TopClean XP™	TopClean XP™	TopClean XP™
Total thickness	ISO 24346 - EN 428	2.10 mm	2.00 mm	2.00 mm
Total weight / m²	ISO 23997 - EN 430	3100	2990	2990
Form of delivery	ISO 24344 - EN 426	Sheet (rolls)		
				approx. 23 running metres x 200 cm

TECHNICAL PERFORMANCES	STANDARDS	Salt & Pepper	Sand	Spaghetti XXL, Spaghetti, Spice & Candy, Havane - Uni, Pastille - Draft
Dimensional stability	ISO 23999 - EN 434			Length + width < 0.10%
Reaction to fire	EN 13501-1			B _{fl} s1 on any A2 _{fl} or A1 _{fl} substrate B _{fl} s1 on any derivative wood substrate
Residual indentation	ISO 24343-1 - EN 433			Required value: ≤ 0.10 mm Average measured value: 0.05 mm
Castor wheel test	ISO 4918 - EN 425			No damage
Furniture leg	EN 424			No damage
Curl resultant to heat	ISO 23999 - EN 434			≤ 8 mm
Electrostatic properties	EN 1815 / EN 1081			< 2 kV on concrete / R ₁ > 10 ⁹ Ω
Hygiene				Does not contribute to infection spreading
Chemical resistance	ISO 26987 - EN 423			High resistance
Thermal resistance	EN 10456			0.02 m² K/W
Underfloor heating				Suitable
Light fastness	EN ISO 105-B02			≥ 6
Slip resistance	DIN 51130 / EN 13893			R9 / μ ≥ 0.3
Colours		12	9	Spaghetti XXL: 2 - Spaghetti: 8 Spice & Candy: 18, Havane: 5 - Uni: 4, Pastille: 2 - Draft: 6